

Distance Sensor


UMF303U035

Part Number



- Digital and analog output
- Stainless steel housing
- Synchronous and multiplex mode
- Temperature drift eliminable

These ultrasonic sensors evaluate the sound reflected by the object. They detect almost every object and are suited especially for the filling level monitoring of fluids or bulk material or the detection of transparent objects. The sensor detects objects independent from their material, aggregate state, color or transparency. The sensors can be adjusted easily by the 4-digit 7-segment display. Convenient programming and quick diagnosis is possible via the IO-Link interface. The sensor can only be used in reflex mode operation.



Technical Data

Ultrasonic Data	
Working Range	200...3000 mm
Measuring Range	2800 mm
Reproducibility maximum	4 mm
Linearity Deviation	4 mm
Resolution	0,3 mm
Ultrasonic Frequency	120 kHz
Opening Angle	< 14 °
Service Life (T = +25 °C)	100000 h
Switching Hysteresis	30 mm

Electrical Data	
Supply Voltage	18...30 V DC
Current Consumption (U _b = 24 V)	< 40 mA
Switching Frequency	3 Hz
Response Time	167 ms
Temperature Range	-30...60 °C
Number of Switching Outputs	1
Switching Output Voltage Drop	< 2,5 V
PNP Switching Output/Switching Current	100 mA
Analog Output	0...10 V
Synchronous Mode	up to 40 sensors
Multiplex Mode	up to 16 sensors
Short Circuit Protection	yes
Reverse Polarity Protection	yes
Overload Protection	yes
Lockable	yes
Interface	IO-Link V1.0
Protection Class	III

Mechanical Data	
Setting Method	Teach-In
Housing Material	Stainless Steel; Plastic
Degree of Protection	IP67
Connection	M12 × 1; 4/5-pin


Safety-relevant Data	
MTTFd (EN ISO 13849-1)	725,66 a

Error Output	●
PNP NO	●
Analog Output	●
IO-Link	●

Connection Diagram No.	184
Control Panel No.	U1
Suitable Connection Equipment No.	2 35
Suitable Mounting Technology No.	130


Complementary Products

Analog Evaluation Unit AW02
Baffle Plate Z0023, Z0024
IO-Link Master
PNP-NPN Converter BG2V1P-N-2M
Software




Ctrl. Panel

U1




60 = display
 80 = Mode Button/Switching Status Indicator
 81 = Plus Button/Error Warning



Legend			
+	Supply Voltage +	nc	Not connected
-	Supply Voltage 0 V	U	Test Input
~	Supply Voltage (AC Voltage)	Ū	Test Input inverted
A	Switching Output (NO)	W	Trigger Input
Ā	Switching Output (NC)	W-	Ground for the Trigger Input
V	Contamination/Error Output (NO)	O	Analog Output
ȳ	Contamination/Error Output (NC)	O-	Ground for the Analog Output
E	Input (analog or digital)	BZ	Block Discharge
T	Teach Input	Amv	Valve Output
Z	Time Delay (activation)	a	Valve Control Output +
S	Shielding	b	Valve Control Output 0 V
RxD	Interface Receive Path	SY	Synchronization
TxD	Interface Send Path	SY-	Ground for the Synchronization
RDY	Ready	E+	Receiver-Line
GND	Ground	S+	Emitter-Line
CL	Clock	±	Grounding
E/A	Output/Input programmable	SnR	Switching Distance Reduction
IO-Link	IO-Link	Rx+/-	Ethernet Receive Path
PoE	Power over Ethernet	Tx+/-	Ethernet Send Path
IN	Safety Input	Bus	Interfaces-Bus A(+)/B(-)
OSSD	Safety Output	La	Emitted Light disengageable
Signal	Signal Output	Mag	Magnet activation
BI_D+/-	Ethernet Gigabit bidirect. data line (A-D)	RES	Input confirmation
ENo RS422	Encoder 0-pulse 0/0 (TTL)	EDM	Contact Monitoring
PT	Platinum measuring resistor	ENAR5422	Encoder A/Ā (TTL)
			Wire Colors according to DIN IEC 60757
			BK Black
			BN Brown
			RD Red
			OG Orange
			YE Yellow
			GN Green
			BU Blue
			VT Violet
			GY Grey
			WH White
			PK Pink
			GNYE Green/Yellow

Characteristic response curve

Characteristic curves show the position of the center of the measured object (100 × 100 mm plate) at the time of switching.



Ob = Object

Sc = Sonic cone width

- Standard
- Medium-width
- Narrow
- Extra-narrow

