

Part number: SLM000002 - Model: SLM-08 NO GM1




Dimension in mm

TECHNICAL CHARACTERISTICS


Sensing distance:	See instructions for installation
Min. liquid specific gravity:	0.75 Kg/dm ³
Max. switching voltage:	230 Vac/dc
Max. switching current:	500 mA
Max. switching power:	50 W/VA
Max. switching frequency:	230 Hz
Output function:	NO
Contact actuation time:	2 mSec
Repeatability (%Sn):	± 0.3
Temperature limits:	-25 ÷ +100 °C
IP rating:	IP 67
Housing material:	AISI 316
Float material:	AISI 316
Connection type:	Cable 0.5 m
Cable type:	2x0.25 mm ² - PVC




MORE THAN SENSORS



Part number: SLM000002 - Model: SLM-08 NO GM1



Part number: SLM000004 - Model: SLM-08 NO GM1 150C




Dimension in mm

TECHNICAL CHARACTERISTICS

Sensing distance:	See instructions for installation
Min. liquid specific gravity:	0.75 Kg/dm ³
Max. switching voltage:	230 Vac/dc
Max. switching current:	500 mA
Max. switching power:	50 W/VA
Max. switching frequency:	230 Hz
Output function:	NO
Contact actuation time:	2 mSec
Repeatability (%Sn):	± 0.3
Temperature limits:	-25 ÷ +100 °C
IP rating:	IP 67
Housing material:	AISI 316
Float material:	AISI 316
Connection type:	Cable 0.5 m
Cable type:	2x1X0.25 mm ² - TEFLON



MORE THAN SENSORS



Part number: SLM000004 - Model: SLM-08 NO GM1 150C